

## TX15150M


## **Electric Driven Pressure Washer**



## TX15150M



**TX** range of electric cold water pressure washers offer an unsurpassed combination of styling and engineering excellence. Manufactured to the highest quality with unbeatable levels of reliability and durability.



Optional Hose Reel



Interpump 44 Series

General	
Weight	43Kg
Dimensions	L860 - W400 - H875 mm
Noise level	LWA 93dB
Stop/Start	Manual Switch
Chemical injection	Low pressure system
Trolley	Thermoplastic, chemical tank & hose holder
Gun & lance	Two piece gun & lance assembly
Nozzle head	Variable angle with high-low pressure
HP hose	8m of 5/16" hose with 22mm couplings
Required water supply	20 Lpm
Max water inlet temp	60° C - 140° F

Pump	
Make	Interpump
Model	44 Series
Flow	15 Lpm
Pressure	150 Bar - 2175 Psi
Lubrication	Oil splash
Materials	Ceramic plungers brass manifold
Speed	2800 Rpm
Drive	Male shaft pump - Hollow shaft motor
Pressure control	Controlset with adjustable pressure
By-pass system	Internal recirculation
Electric Motor	
Electric Motor	
Power	415 Volts, 5kW, 50Hz, 8.5 Amps
Motor Protection	Thermal Protection to IPX5

Class F

Length - 5m, Wire gauge - 2.5mm<sup>2</sup>/14AWG

HP Pump Services Unit 32 Wynford Industrial Estate Romsey Hampshire SO51 0PW Tel: 01794 367477 www.hppumpservices.co.uk

Insulation

**Power Cable**