

TX500-21200M

Electric Driven Pressure Washer



TX500-21200M



TX range of electric cold water pressure washers offer an unsurpassed combination of styling and engineering excellence. Manufactured to the highest quality with unbeatable levels of reliability and durability.



Integrated Hose Reel



Interpump 47 Series

General	
Weight	92Kg (Dry) - 115Kg (Max)
Dimensions	L825 - W495 - H860 mm
Noise level	LWA 92dB
Stop/Start	Automatic Switch with 20s delay
Chemical injection	Low pressure system
Trolley	Thermoplastic, chemical tank & hose holder
Gun & lance	Two piece gun & lance assembly
Nozzle head	Variable angle with high-low pressure
HP hose	15m of 5/16" hose with 22mm couplings
Required water supply	23 Lpm
Max water inlet temp	60° C - 140° F

Pump	
Make	Interpump
Model	47 Series
Flow	21 Lpm
Pressure	200 Bar - 2900 Psi
Lubrication	Oil splash
Materials	Ceramic plungers brass manifold
Speed	1450 Rpm
Drive	Male shaft pump with flexible coupling
Pressure control	Controlset with adjustable pressure
By-pass system	Internal recirculation
Electric Motor	
Power	415 Volts, 9kW, 50Hz, 17 Amps

Electric Motor	
Power	415 Volts, 9kW, 50Hz, 17 Amps
Motor Protection	Thermal Protection to IPX5
Insulation	Class F
Power Cable	Length - 5m, Wire gauge - 2.5mm² / 14AWG

HP Pump Services Unit 32 Wynford Industrial Estate Romsey Hampshire SO51 0PW Tel: 01794 367477 www.hppumpservices.co.uk